

Multi roof mount antenna 810 – 2170 MHz

- One antenna only for world-wide application AMPS, DoCoMo, GSM 900/1800, PCS, DCS 1800/1900, UMTS).
- Made for future technologies, UMTS operation included.
- Excellent omni-directional pattern.
- Ultra broadband design with no tuning necessary.



K 70 55 64

Type No. K 70 55 64
Ord. No. 510 934

Frequency range	824 – 896 MHz 810 – 958MHz 890 – 960 MHz 1710 – 1880 MHz 1850 – 1990 MHz 1900 – 2170 MHz
AMPS	
DoCoMo	
GSM 900	
GSM 1800	
GSM 1900	
UMTS	
	typ. 0 dB gain (ref. to quarter-wave whip), length 89 mm
Connection	Minicrimp (male)
Maximum load	
AMPS	3 W
DoCoMo	0.8 W
GSM 900	8 W
GSM 1800	2 W
GSM 1900	2 W
UMTS	2 W
	(at 50 °C ambient temperature)
Mounting location	Car roof recommended
Mounting	Into bore hole 18 ⁺¹ mm diameter from the external side of the car body. Into bore hole 14 ... 19 mm diameter from the inner side of the car body.
Built-in depth	12 mm
Max. diameter at base	32 mm
Antenna length	89 mm
Material	Weather resistant plastic parts; all visible metal parts are black chromium-plated.
Contents of delivery	Whip, base, antenna wrench.
Accessories	
Spare whip	Ord. No. 510 964